

ADVANCED PLACEMENT PHYSICS MECHANICS TABLE OF INFORMATION

CONSTANTS AND CONVERSION FACTORS		
Universal gravitational constant, $G = 6.67 \times 10^{-11} \text{ m}^3/(\text{kg} \cdot \text{s}^2) = 6.67 \times 10^{-11} \text{ N} \cdot \text{m}^2/\text{kg}^2$		
Acceleration due to gravity at Earth's surface, $g = 9.8 \text{ m/s}^2$		
Magnitude of the gravitational field strength at the Earth's surface, $g = 9.8 \text{ N/kg}$		

PREFIXES		
Factor	Prefix	Symbol
10^{12}	tera	T
10^9	giga	G
10^6	mega	M
10^3	kilo	k
10^{-2}	centi	c
10^{-3}	milli	m
10^{-6}	micro	μ
10^{-9}	nano	n
10^{-12}	pico	p

UNIT SYMBOLS	hertz, Hz	newton, N
	joule, J	second, s
	kilogram, kg	watt, W
	meter, m	

VALUES OF TRIGONOMETRIC FUNCTIONS FOR COMMON ANGLES							
θ	0°	30°	37°	45°	53°	60°	90°
$\sin \theta$	0	$1/2$	$3/5$	$\sqrt{2}/2$	$4/5$	$\sqrt{3}/2$	1
$\cos \theta$	1	$\sqrt{3}/2$	$4/5$	$\sqrt{2}/2$	$3/5$	$1/2$	0
$\tan \theta$	0	$\sqrt{3}/3$	$3/4$	1	$4/3$	$\sqrt{3}$	∞

The following assumptions are used in this exam.

- The frame of reference of any problem is assumed to be inertial unless otherwise stated.
- Air resistance is assumed to be negligible unless otherwise stated.
- Springs and strings are assumed to be ideal unless otherwise stated.

MECHANICS			
$v_x = v_{x0} + a_x t$	$a = \text{acceleration}$	$\omega = \frac{d\theta}{dt}$	$a = \text{acceleration}$
$x = x_0 + v_{x0}t + \frac{1}{2}a_x t^2$	$E = \text{energy}$	$\alpha = \frac{d\omega}{dt}$	$d = \text{distance}$
$v_x^2 = v_{x0}^2 + 2a_x(x - x_0)$	$f = \text{frequency}$	$\omega = \omega_0 + \alpha t$	$f = \text{frequency}$
$\Delta x = \int v_x(t) dt$	$F = \text{force}$	$\theta = \theta_0 + \omega_0 t + \frac{1}{2}\alpha t^2$	$F = \text{force}$
$\Delta v_x = \int a_x(t) dt$	$h = \text{height}$	$\omega^2 = \omega_0^2 + 2\alpha(\theta - \theta_0)$	$I = \text{rotational inertia}$
$\vec{x}_{\text{cm}} = \frac{\sum m_i \vec{x}_i}{\sum m_i}$	$J = \text{impulse}$	$v = r\omega$	$k = \text{spring constant}$
$\vec{r}_{\text{cm}} = \frac{\int \vec{r} dm}{\int dm}$	$k = \text{spring constant}$	$a_r = r\alpha$	$K = \text{kinetic energy}$
$\lambda = \frac{d}{d\ell} m(\ell)$	$K = \text{kinetic energy}$	$\vec{\tau} = \vec{r} \times \vec{F}$	$\ell = \text{length}$
$\vec{a}_{\text{sys}} = \frac{\sum \vec{F}}{m_{\text{sys}}} = \frac{\vec{F}_{\text{net}}}{m_{\text{sys}}}$	$\ell = \text{length}$	$I_{\text{tot}} = \sum I_i = \sum m_i r_i^2$	$L = \text{angular momentum}$
$ \vec{F}_g = G \frac{m_1 m_2}{r^2}$	$m = \text{mass}$	$I = \int r^2 dm$	$m = \text{mass}$
$ \vec{F}_f \leq \mu \vec{F}_N$	$M = \text{mass}$	$I' = I_{\text{cm}} + M d^2$	$M = \text{mass}$
$\vec{F}_s = -k \Delta \vec{x}$	$p = \text{momentum}$	$\alpha_{\text{sys}} = \frac{\sum \tau}{I_{\text{sys}}} = \frac{\tau_{\text{net}}}{I_{\text{sys}}}$	$p = \text{momentum}$
$a_c = \frac{v^2}{r} = r\omega^2$	$P = \text{power}$	$K_{\text{rot}} = \frac{1}{2} I \omega^2$	$r = \text{radius, distance, or position}$
$T = \frac{1}{f}$	$r = \text{radius, distance, or position}$	$W = \int \tau \cdot d\theta$	$t = \text{time}$
$K = \frac{1}{2}mv^2$	$t = \text{time}$	$\vec{L} = \vec{r} \times \vec{p} = I \vec{\omega}$	$T = \text{period}$
$W = \int_a^b \vec{F} \cdot d\vec{r}$	$T = \text{period}$	$\Delta L = \int \tau dt$	$v = \text{velocity or speed}$
$\Delta K = \sum W_i = \sum F_{\parallel,i} d_i$	$\mu = \text{coefficient of friction}$	$\Delta x_{\text{cm}} = r \Delta \theta$	$W = \text{work}$
$\Delta U = - \int_a^b \vec{F}_{\text{ef}}(r) \cdot d\vec{r}$		$T = \frac{2\pi}{\omega} = \frac{1}{f}$	$x = \text{position or distance}$
$F_x = -\frac{dU(x)}{dx}$	$P_{\text{avg}} = \frac{W}{\Delta t} = \frac{\Delta E}{\Delta t}$	$T_s = 2\pi \sqrt{\frac{m}{k}}$	$\alpha = \text{angular acceleration}$
$U_s = \frac{1}{2}k(\Delta x)^2$	$P_{\text{inst}} = \frac{dW}{dt}$	$T_p = 2\pi \sqrt{\frac{\ell}{g}}$	$\theta = \text{angle}$
$U_G = -G \frac{m_1 m_2}{r}$	$\vec{p} = m\vec{v}$	$T_{\text{phys}} = 2\pi \sqrt{\frac{I}{mgd}}$	$\tau = \text{torque}$
$\Delta U_g = mg\Delta y$	$\vec{F}_{\text{net}} = \frac{d\vec{p}}{dt}$	$x = x_{\text{max}} \cos(\omega t + \phi)$	$\phi = \text{phase angle}$
	$\vec{J} = \int_{t_1}^{t_2} \vec{F}_{\text{net}}(t) dt = \Delta \vec{p}$		$\omega = \text{angular frequency}$
	$\vec{v}_{\text{cm}} = \frac{\sum \vec{p}_i}{\sum m_i} = \frac{\sum m_i \vec{v}_i}{\sum m_i}$		or angular speed

ADVANCED PLACEMENT PHYSICS ELECTRICITY AND MAGNETISM
TABLE OF INFORMATION

CONSTANTS AND CONVERSION FACTORS		UNIT SYMBOLS
Coulomb constant,	$k = \frac{1}{4\pi\epsilon_0} = 9.0 \times 10^9 \frac{\text{N} \cdot \text{m}^2}{\text{C}^2}$	ampere, A
Vacuum permittivity,	$\epsilon_0 = 8.85 \times 10^{-12} \frac{\text{C}^2}{(\text{N} \cdot \text{m}^2)}$	coulomb, C
Vacuum permeability,	$\mu_0 = 4\pi \times 10^{-7} \frac{\text{T} \cdot \text{m}}{\text{A}}$	electron volt, eV
Proton mass,	$m_p = 1.67 \times 10^{-27} \text{ kg}$	farad, F
Neutron mass,	$m_n = 1.67 \times 10^{-27} \text{ kg}$	henry, H
Electron mass,	$m_e = 9.11 \times 10^{-31} \text{ kg}$	hertz, Hz
Elementary charge,	$e = 1.60 \times 10^{-19} \text{ C}$	joule, J
1 electron volt,	$1 \text{ eV} = 1.60 \times 10^{-19} \text{ J}$	kilogram, kg
Speed of light,	$c = 3.00 \times 10^8 \text{ m/s}$	meter, m
1 unified atomic mass unit,	$1 \text{ u} = 1.66 \times 10^{-27} \text{ kg} = 931 \text{ MeV}/c^2$	newton, N
Universal gravitational constant, $G = 6.67 \times 10^{-11} \frac{\text{m}^3}{(\text{kg} \cdot \text{s}^2)} = 6.67 \times 10^{-11} \frac{\text{N} \cdot \text{m}^2}{\text{kg}^2}$		ohm, Ω
Magnitude of the acceleration due to gravity at Earth's surface, $g = 9.8 \text{ m/s}^2$		second, s
Magnitude of the gravitational field strength at Earth's surface, $g = 9.8 \text{ N/kg}$		tesla, T
		volt, V
		watt, W


PREFIXES		
Factor	Prefix	Symbol
10^{12}	tera	T
10^9	giga	G
10^6	mega	M
10^3	kilo	k
10^{-2}	centi	c
10^{-3}	milli	m
10^{-6}	micro	μ
10^{-9}	nano	n
10^{-12}	pico	p

VALUES OF TRIGONOMETRIC FUNCTIONS FOR COMMON ANGLES							
θ	0°	30°	37°	45°	53°	60°	90°
$\sin \theta$	0	$1/2$	$3/5$	$\sqrt{2}/2$	$4/5$	$\sqrt{3}/2$	1
$\cos \theta$	1	$\sqrt{3}/2$	$4/5$	$\sqrt{2}/2$	$3/5$	$1/2$	0
$\tan \theta$	0	$\sqrt{3}/3$	$3/4$	1	$4/3$	$\sqrt{3}$	∞

The following conventions are used in this exam:

- The frame of reference of any problem is assumed to be inertial unless otherwise stated.
- Air resistance is assumed to be negligible unless otherwise stated.
- Springs and strings are assumed to be ideal unless otherwise stated.
- The electric potential is zero at an infinite distance from an isolated point charge.
- The direction of current is the direction in which positive charges would drift.
- All batteries, wires, and meters are assumed to be ideal unless otherwise stated.

ELECTRICITY AND MAGNETISM		
$\left \vec{F}_E \right = \frac{1}{4\pi\epsilon_0} \frac{ q_1 q_2 }{r^2} = k \frac{ q_1 q_2 }{r^2}$ $\vec{E} = \frac{\vec{F}_E}{q}$ $\vec{E} = \frac{1}{4\pi\epsilon_0} \int \frac{dq}{r^2} \hat{r}$ $\Phi_E = \int \vec{E} \cdot d\vec{A}$ $\oint \vec{E} \cdot d\vec{A} = \frac{q_{\text{enc}}}{\epsilon_0}$ $Q_{\text{total}} = \int \rho(r) dV$ $U_E = \frac{1}{4\pi\epsilon_0} \frac{q_1 q_2}{r}$ $V = \frac{1}{4\pi\epsilon_0} \int \frac{dq}{r}$ $\Delta V = - \int_a^b \vec{E} \cdot d\vec{r}$ $E_x = - \frac{dV}{dx}$ $\Delta U_E = q \Delta V$ $C = \frac{Q}{\Delta V}$ $C = \frac{\kappa \epsilon_0 A}{d}$ $U_C = \frac{1}{2} Q \Delta V$ $\kappa = \frac{\epsilon}{\epsilon_0}$ $I = \frac{dq}{dt}$ $I = \int \vec{J} \cdot d\vec{A}$ $\vec{E} = \rho \vec{J}$ $R = \frac{\rho \ell}{A}$ $I = \frac{\Delta V}{R}$ $P = I \Delta V$	<p><i>A</i> = area <i>C</i> = capacitance <i>d</i> = distance <i>E</i> = electric field <i>F</i> = force <i>I</i> = current <i>J</i> = current density <i>ℓ</i> = length <i>P</i> = power <i>q</i> = charge <i>Q</i> = charge <i>r</i> = radius, distance, or position <i>R</i> = resistance <i>t</i> = time <i>U</i> = potential energy <i>V</i> = electric potential or volume ϵ = electric permittivity ρ = resistivity or charge density κ = dielectric constant Φ = flux</p>	$R_{\text{eq},s} = \sum_i R_i$ $\frac{1}{R_{\text{eq},p}} = \sum_i \frac{1}{R_i}$ $\frac{1}{C_{\text{eq},s}} = \sum_i \frac{1}{C_i}$ $C_{\text{eq},p} = \sum_i C_i$ $\tau = R_{\text{eq}} C_{\text{eq}}$ $\oint \vec{B} \cdot d\vec{A} = 0$ $\vec{F}_B = q(\vec{v} \times \vec{B})$ $d\vec{B} = \frac{\mu_0}{4\pi} \frac{I(d\vec{\ell} \times \hat{r})}{r^2}$ $\vec{F}_B = \int I(d\vec{\ell} \times \vec{B})$ $\oint \vec{B} \cdot d\vec{\ell} = \mu_0 I_{\text{enc}}$ $B_{\text{sol}} = \mu_0 n I$ $\Phi_B = \int \vec{B} \cdot d\vec{A}$ $\mathcal{E} = \oint \vec{E} \cdot d\vec{\ell} = - \frac{d\Phi_B}{dt}$ $ \mathcal{E}_{\text{sol}} = N \left \frac{d\Phi_B}{dt} \right $ $L_{\text{sol}} = \frac{\mu_{\text{core}} N^2 A}{\ell}$ $U_L = \frac{1}{2} L I^2$ $\mathcal{E} = -L \frac{dI}{dt}$ $\tau = \frac{L}{R_{\text{eq}}}$ $\omega_{LC} = \frac{1}{\sqrt{LC}}$

GEOMETRY AND TRIGONOMETRY							
Rectangle	Rectangular Solid			A = area	b = base	C = circumference	Right Triangle
$A = bh$	$V = \ell wh$						$a^2 + b^2 = c^2$
Triangle	Cylinder			$\sin \theta = \frac{a}{c}$			
$A = \frac{1}{2}bh$	$V = \pi r^2 \ell$			$\cos \theta = \frac{b}{c}$			
Circle	Sphere			$\tan \theta = \frac{a}{b}$			
$A = \pi r^2$	$V = \frac{4}{3}\pi r^3$						
$C = 2\pi r$	$S = 4\pi r^2$						
$s = r\theta$							

VECTORS	CALCULUS	IDENTITIES
$\vec{A} \cdot \vec{B} = AB \cos \theta$ $ \vec{A} \times \vec{B} = AB \sin \theta$ $\vec{r} = (A\hat{i} + B\hat{j} + C\hat{k})$ $\vec{C} = \vec{A} + \vec{B}$ $\vec{C} = (A_x + B_x)\hat{i} + (A_y + B_y)\hat{j}$	$\frac{df}{dx} = \frac{df}{du} \frac{du}{dx}$ $\frac{d}{dx}(x^n) = nx^{n-1}$ $\frac{d}{dx}(e^{ax}) = ae^{ax}$ $\frac{d}{dx}(\ln ax) = \frac{1}{x}$ $\frac{d}{dx}[\sin(ax)] = a \cos(ax)$ $\frac{d}{dx}[\cos(ax)] = -a \sin(ax)$ $\int x^n dx = \frac{1}{n+1}x^{n+1}, n \neq -1$ $\int e^{ax} dx = \frac{1}{a}e^{ax}$ $\int \frac{dx}{x+a} = \ln x+a $ $\int \cos(ax) dx = \frac{1}{a} \sin(ax)$ $\int \sin(ax) dx = -\frac{1}{a} \cos(ax)$	$\log(a \cdot b^x) = \log a + x \log b$ $\sin^2 \theta + \cos^2 \theta = 1$ $\sin(2\theta) = 2 \sin \theta \cos \theta$ $\frac{\sin \theta}{\cos \theta} = \tan \theta$